

## HEAVY OIL SPECIFICATION SHEET

<u>Test</u>	<u>Unit</u>	<u>Range</u>			<u>ASTM Method</u>
		<u>Normal</u>	<u>Min</u>	<u>Max</u>	
Flash point	°C	81.00	66.00	96.00	D-92
Pour Point	°C	-21.00	-30.00	-12.00	D-97
Water & Sedimentation	%, Vol	0.09	0.03	0.30	D-2709
Ash	%, m/m	0.03	0.00	0.07	D-482
Viscosity at 40 °C	SSF	16.60	10.70	24.00	D-445, D-88
Viscosity at 100 °C	Cst	3.80	2.20	4.80	D-445
Density at 15 °C	Kg/m <sup>3</sup>	900.90	885.60	923.70	D-1298
Carbon Residue	%, m/m	4.99	2.97	16.25	D-524

**Note\***

All values are taken on samples of one batch and the specification may vary from batch to batch. Buyers are requested to kindly demand the specifications of the specific batch they will purchase.

1221 Bowers St. # 1432  
Birmingham, Michigan 48012-1432  
U.S.A.

• • • • •  
Tel: 248.723.6844  
Fax: 248.282.0520  
E-mail: Info@USEnergyResources.net  
www.usenergyResources.net